

CEM DESFire Smart Card

Pre-personalised Contactless Smart card


OVERVIEW

The CEM DESFire 13.56MHz read/write contactless smart card can be used for a range of different applications from access control to other applications such as cashless vending and public transportation. Using a standardised Mifare Application Directory (MAD), the card contains a structured file system offering security for multiple applications and to support future growth.

Utilising 3DES (Triple DES) encryption, the CEM DESFire card information is securely stored on the card, ensuring that the card cannot be cloned and that only valid cards are granted access.

The CEM DESFire smart card delivers the perfect balance of speed, performance and cost efficiency when opting for a DESFire smart card solution. Featuring an on-chip backup management system and mutual three pass authentication, the CEM DESFire smart card is based on MiFare DESFire EV1 and can hold up to 28 different applications and 32 files per application.

The size and access conditions of each file are defined at the moment of its creation, making the CEM DESFire Smart card a truly flexible and convenient product.



CEM DESFire smart card

FEATURES

- Utilises highly secure 13.56MHz MiFare DESFire smart card technology
- Pre-personalised card memory allowing for usage in other systems such as cashless vending
- Triple DES (3DES) encryption between the card and the reader
- Compatible with the CEM sPass reader and DCM 350 two-door controller, as well as S610 reader range
- Meets ISO standards for thickness for use with all direct image and thermal transfer printers
- Add a magnetic stripe, barcode, anti-counterfeiting, or photo ID to the card
- Fully ISO / IEC 14443 A 1-4 compliant
- Available for use on CEM readers: S610e, S610s, S610f fingerprint reader & sPass reader

PRODUCT HIGHLIGHTS

Markets Served

The CEM DESFire Smart card is suited to many different applications such as security management systems, cashless vending in schools, universities and offices and public transport including payment onto buses, trains or trams.

Convenience and cost effective

CEM DESFire smart card memory is pre-personalised for customer convenience. Unique and highly secure keys between the card and the AC2000 system are pre configured. As keys are managed by the system, there are no programming cards required. With ready made encryption, the CEM DESFire card offers customers a flexible and quick smart card solution, without the cost of card personalisation and key/filing management.

For additional flexibility, the DESFire smart card also comes with blank and unused memory keys that can be used for other applications, for example cashless vending and printing.

Secure

The CEM DESFire Smart card comes with a flexible filing system based on applications and files contained within the

applications. Each card will have one Master Key, and up to 14 keys per application. Keys include control of Read (Debit), Write (Debit/Limited Credit), R&W, and Change Configuration.

Specifications:

2-8K bytes EEPROM

28 applications

16 or 32 files per application

Meets Industry Standards

The CEM DESFire Smart card adheres to strict industry standards for physical design, communications and encryption. Some of these include; 14443 for contactless communications, ICA09303Pt-Vol2 Machine Readable Travel Documents, ISO/IEC 7812 Identification cards - Identification of issuers, ISO/IEC 7816-4 BER-TLV, ISO/IEC 7816-6:2004 Inter-industry data elements for interchange, TS 1000-1 Interoperable public transport ticketing using contactless smart customer media, PIV Interoperability For Non-Federal Issuers, and RFC 4122 - A Universally Unique Identifier (UUID) URN Namespace.

TECHNICAL SPECIFICATIONS

TYPICAL MAXIMUM READ RANGE

S610e DESFire reader	- 4cm
S610s DESFire reader	- 4cm
S610f DESFire fingerprint reader	- 4cm
sPass DESFire reader	- 4cm

Dimensions	2.127" x 3.375" x 0.033" max (5.40 x 8.57 x 0.084 cm) Can be carried with credit cards in a wallet or purse. Use with a strap and clip as a photo ID badge
------------	--

Weight	0.20oz (5.7 g)
--------	----------------

Card Construction	Thin, flexible polyvinyl chloride (PVC) laminate.
-------------------	---

Operating Temperature	-13° to 122° F (-25° to 50° C)
-----------------------	--------------------------------

Operating Frequency	13.56 MHz
---------------------	-----------

Transaction Time	89 ms typical
------------------	---------------

Baud Rate	High data rates according to ISO / IEC 14443-4 106 to 848 Kbit/s
-----------	---

Write Endurance	500,000 cycles
-----------------	----------------

Data Retention	10 years
----------------	----------

Memory Type	EEPROM, read/write
-------------	--------------------

Photo ID Compatible
Cards are supplied blank. However customers can print directly onto the card with a direct image or thermal transfer printer. For custom pre-printed artwork contact CEM Systems for prices.

Durability	Strong, flexible, and resistant to cracking and breaking.
------------	---

Description	13.56 MHz contactless smart card
-------------	----------------------------------

PRODUCT CODES

CRD/218/002	CEM DESFire Card 2k byte
CRD/218/004	CEM DESFire Card 4k byte
CRD/218/008	CEM DESFire Card 8k byte

Product specifications and availability is subject to change without notice. Certain product names mentioned herein may be trade names and/or registered trademarks of their companies.