

AC2000 MatriVideo Interface

Instek Digital Video



Features That Make a Difference:

- Seamless integration with Instek MatriVideo 2U hDVR and 2U NVR products
- Associate access control alarms with digital video footage
- Live video feed activated directly from AC2000 Security Hub application
- Live video pop-up based on priority or time
- Real time visual tracking and recording during alarm conditions
- Camera icons can be positioned in AC2000 Security Hub alongside access control readers
- Display up to 16 individual camera feeds simultaneously in a single screen virtual matrix
- Adjust camera pan, tilt, and zoom via integral software control

The AC2000 video interface for Instek Digital MatriVideo provides the ability to associate access control alarms with MatriVideo digital video clips, as well as to view live camera footage. This enables AC2000 to act as the central Security Management System (SMS).

AC2000 seamlessly integrates with MatriVideo, giving the operator a range of video related facilities to generate alarm reports with recorded video playback. The interface also allows system operators to view live video feed, configure live video popup on alarm, export video playback clips, take video snapshots and control camera positioning and presets.

The high level two way system allows a user to fully integrate the power of a MatriVideo system into the central AC2000 Security Hub application. AED enables all alarms, events and associated camera footage to be displayed centrally on the AC2000 system.

Alarms with associated video

If an alarm event contains associated video footage, the operator can access the footage within AC2000 Security Hub which will activate the DVR Viewer application.

Once DVR Viewer has launched, the actual video footage is then downloaded from the MatriVideo system. The viewer window will automatically display the video playback from the start of the footage. Standard video controls are available on DVR Viewer to Play, Pause, and Fast Forward/Rewind.

Additionally system operators can view archived video footage by running alarms reports in the AC2000 Extended Reports application.

Recorded Video Search and Retrieve

DVR Viewer also allows the user to search for alarms with video footage using various criteria which can then be replayed by clicking on the requested alarm detail.

Camera control

A camera control facility is available for moveable cameras such as dome-based devices.

The following controls are available:

- Iris, Zoom and Focus Controls
- Camera Preset Selection
- Pan + Tilt Control
- Auto-Iris Selection
- Auto-Pan
- Auto-Focus

Live video feed

The operator can split the video screen into 1x1, 2x2 (4), 3x3 (9) or 4x4 (16) options allowing the operator to view live footage from up to sixteen cameras simultaneously, each in its separate pane.

Each pane can be simply configured using a drag and drop facility to place the appropriate camera into the required pane.

Live video pop-up

Using the Video Popup application, live video is available based on alarm priority or time. This allows instant access to live video for certain alarms and is used with a queuing system.

This allows the operator to easily view live feeds when multiple alarms are received.

Requirements

- Security Hub and Video Viewer available from AC2000 v7.1 Service Pack 1 upwards
- AC2000 v7 software
- Please contact your CEM account representative to compatible Matrivideo products

Ordering Information

Product Code	Description
SWVINT-MATRI	AC2000 MatriVideo Interface

Related Products



AC2000

www.cemsys.com