

emerald TS100f

Intelligent Fingerprint Terminal Fully Integrated Biometric Solution



Key Features

- Multifunctional access terminal with integrated biometrics
- Controller, advanced IP card reader and single biometric solution all in one that meets requirements for three stage identity authentication (card, PIN, and biometric verification)
- Fast card and fingerprint verification, uses 1:1 fingerprint match at the door
- Secure storage of fingerprints on the central AC2000 server and on the emerald internal database
- Fingerprint module gives a high resolution scan with FIPS201 approved biometric algorithm
- Durable enough for indoor or outdoor usage with an IK06 vandal resistance rating, and IP65 dust and water resistant rating
- User-friendly 4.3" capacitive LCD touch screen

emerald TS100f is a multifunctional touch screen access terminal with fully integrated biometric. Used in conjunction with CEM Systems AC2000 security management system, the emerald TS100f uniquely provides users with a wide range of functions, all in one powerful device that controls access to restricted areas where an additional biometric layer of security is required.

Featuring a controller, advanced IP card reader and single biometric solution all in one, the emerald TS100f meets requirements for three stage identity authentication (card, PIN, and biometric verification) using one device.

The emerald TS100f has a bright 4.3" graphical LCD touch screen to display predefined messages and icons to cardholders depending on access privileges. Its built in mini PIR sensor provides energy saving motion detection and a multi-coloured LED provides users with a visual indication of access status. With hardened glass and an antiglare coating, the emerald TS100f is durable for indoor and outdoor use.

Off-Line Card Validation

The emerald TS100f has a large internal database that enables it to operate in off-line mode. In off-line mode the terminal can hold up to 123,000 card holder records with 2 fingerprint templates for each card holder.

PIN & Fingerprint

This special emerald enhancement allows using emerald TS100f terminal without a card, where the user must enter their special designated 6-digit PIN number followed by a fingerprint verification. Where necessary, this removes the need for a physical card while maintaining a high level of security at the door

Fully integrated biometrics & access control solution

The emerald TS100f features a controller, advanced IP card reader and fingerprint module all in one device.

Key Features Continues

- Intuitive Graphical User Interface enhancing user experience at the door
- Scramble keypad option for Personal Identification Number (PIN)
- Available with onboard PoE+ technology to power the terminal and additional door furniture
- PIR motion detection
- Remote upload of new firmware directly to the reader with on-screen indication
- Maintenance Information / Security Intelligence Point
- Ability to display live video at the workstation on intercom request, when interfaced with CCTV system (available with AC2000 v6.7 & upwards)
- Ability to display advertising/ information announcements and personal messages

Checklist Mode

The emerald intelligent access terminal features the ability to create a series of user defined questions and associated images that cardholders must answer positively to before access is granted. This feature can be used to improve company compliance and for health and safety enforcement. For example, staff may require personal protection equipment (PPE) before entering a restricted or hazardous zone, which can be included as a reminder as part of an emerald checklist.

The selections made by users of Checklist mode are stored on the AC2000 server, also recording the questions which receive a Negative answer.

Time & Attendance

In T&A mode, the emerald allows users to select either the IN or OUT transaction on a single terminal, before swiping their cards. Depending on the selection, the emerald will allocate valid transactions against either the IN or OUT swipe. System administrators can then easily report on the T&A activity using AC2000 Time and Attendance module or system reports. For highly secure locations, Time & Attendance mode can work in conjunction with Fingerprint verification and other modes such as PIN or Image on Swipe. (T&A is a dedicated door mode. emerald will not control door access when in T&A mode.)

PIN as Card

PIN as Card is a special emerald feature, offering cardless verification using a unique 6 digit PIN to verify transactions. Where necessary, this removes the need for a physical card while maintaining security at the door.

Single process & network solution

Fingerprint enrolment is captured and stored via the AC2000 access control system at the same time as cardholder enrolment. This offers clients a single solution and eradicates the requirement to purchase a separate biometric reader and software application to link to the access control system.

Power over Ethernet Plus

The emerald TS100f is available with onboard Power over Ethernet Plus (PoE+) technology allowing the terminal and additional door furniture* to be powered using a single Cat 5e/6 cable at the door.

Multi Date Check

The TS200 is designed to be easy to install, without the requirement for specialist tools. Installers simply assign an IP address via the terminal's user friendly interface, which then connects automatically to the AC2000 server over an Ethernet network. Once powered, the terminal self configures and quickly receives a full cardholder database.

Multi Date Check

As an additional safety and security layer applied on top of system card validity checks, this mode allows the emerald to check the validity of any additional criteria such as training certificates or contracts that might be required at the site. System administrators can easily configure Multi Date Check using the dedicated intuitive AC2000 Web interface and run detailed reports on the configured Multi Date Check criteria and expiry dates, to ensure that personnel's certificates and permissions stay up to date. Whether it's applied for an individual cardholder or company-wide, additional date checks will take place after a valid transaction and a detailed result message will be displayed on emerald screen. This feature is only available with AC2000 v7.0 and above.

Emerald Link

Emerald link allows operators to activate passenger mode at both sides of the door while providing visual feedback of the remaining passenger time. Emerald Link is the deployment of two emeralds back to back in passenger mode to control a single door. The emeralds communicate with each other over Ethernet using secure 128-bit AES encryption. Alarms generated on either emerald are visually displayed on both sides of the door.

Specifications

Physical	
Size	240 x 108 x 49mm (At widest point)
Weight	600g (approx.)
Housing	Flame retardant polycarbonate, with UV stabilisation. RoHS compliant, and PBE/ PBDE free flame retardant system
LCD	Capacitive, light touch, 4.3" Diagonal, 480 x 272 square pixel 16 bit colour
LED Indicator	High Intensity multi-colour LED indicator
Colour	Black
Voltage	10-14V DC
Power	
PoE Version	when powered from IEEE802.af compliant source
Current	350 - 550mA (Typical) 860mA (Peak)
Current available to power door furniture	None
PoE+ Version	when powered from IEEE802.at source
Current	350 - 550mA (Typical) 860mA (Peak)
Current available to power door furniture	650mA @12V*
Environmental	
IP Rating	IP65
IK Rating	IK06
Temperature	-15° to 50°C **
Fingerprint***	
Type	Optical
Resolution	500 dpi
Sensing area	16mm x 19.0mm
Image size (pixels)	272x320
EER	< 0.1%
Functionality	
Inputs	Four analog inputs – voltage provided
Outputs	2 relays volt free contacts (dry contact)
Switchable wet outputs	
Rating	Internal : Internal: 12Vdc @ 1.3A External: Up to 30Vdc @ 2A (60W)
Memory	128 MB RAM, 256MB NAND Flash
Expansion	Micro SD slot for optional memory expansion. Micro SD card fitted.
RTC Battery Backup	3.0V rechargeable Lithium-ion
Off-line Database	
Cardholders	123,000 (two fingerprint templates per cardholder)
Transactions	Up to 50,000
Card technologies	MIFARE (CSN), DESFire (CSN), CEM DESFire 3DES, CEM DESFire AES, iCLASS, iCLASS SE, PicoPass

Communication Interface	
To Exit Reader	RS485 (CEM S610 Exit Reader/ CEM S700 Exit Reader) Wiegand (3rd party read heads)
Cable Connection	M3 Screw terminals
To System Host	10/100 Base-T TCP/IP using CAT5e Unshielded twisted pair cable
Cable Connection	RJ45
Operating Modes	Door Mode, Interlock, Control Post, Passenger, Multi-swipe, Global PIN, Entry Checklist Mode
Special Features	533 MHz DSP FIPS201 approved algorithm Robust optical Solid and scratch-free sensor surface Reliable high quality fingerprint image for wet & dry fingers Sensor automatically optimises fingerprint image
Verification time (1:1)	< 0.55 sec

* Only PoE+ IEEE802.at provides power for both the terminal and additional door furniture (current available to power door furniture: 650mA). Power requirements beyond this limit will require the DIU230

** Biometric verification performance and accuracy can vary, subject to environmental conditions such as ice, snow etc.

*** Equal Error Rate. Manufacturer's data related to fingerprint match only. EER is dependent on databases

Ordering Information

Product Code	Description
TSR/100/115	emerald TS100f Intelligent Fingerprint Terminal (MIFARE CSN/DESFire CSN/CEM DESFire)
TSR/100/118	emerald TS100f Intelligent Fingerprint Terminal (iCLASS / iCLASS SE)

To order contact cem.sales@tycoint.com or call +44(0) 2890 456 767

Requirements

- AC2000 Airport v7.0 and upwards
- AC2000 v7.0 and upwards
- AC2000 Lite v7.0 and upwards
- CEM S610f Validation Reader
- RTC Ethernet Reader Controller or Suprema BioMini Plus 2 USB 2.0 Fingerprint Validation Scanner (Fingerprint Capture Only)

Related Products



- AC2000
- AC2000 Airport
- AC2000 Lite

emerald

About Johnson Controls

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit www.cemsys.com or follow CEM Systems on LinkedIn and Twitter.

© 2021 Johnson Controls. All rights reserved. Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

CEM/B/380 Rev B

The power behind **your mission**

